

KEP1030F

beyond
the best

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description	Features
KEP1030F is an EPDM rubber with narrow molecular weight distribution, medium ethylene contents. It can be used to Heat-resistance hose, washing machine hose, window seals and Various type of automobile parts.	<ul style="list-style-type: none">- High Mooney Viscosity- High filler loading & Good physical property- High curing speed- Good Extrusion properties- Good low temperature properties

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+8)@125 °C	86.0 ± 6.0	MU	ASTM D1646
Ethylene Contents	61.5 ± 3.0	wt %	ASTM D3900
ENB Contents	4.5 ± 1.0	wt %	ASTM D6047

Other Products Features

Product Form	Bale
Packaging	25 kg/Bag in Carton & Mesh Box, LDPE film, 750 kg(25 kg × 30)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
Revision Date	12/02/2020
Revision No.	10