

## Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

### Product Data Sheet

Product Description	Features
KEP2480 is an EPDM rubber with bimodal molecular weight distribution, low ethylene contents, high ENB contents. It can be used to weather strip seals, CV sponge and co-extruded sponge.	<ul style="list-style-type: none"><li>- High loadability</li><li>- Excellent processability</li><li>- Fast curing speed</li><li>- Good curing performance</li></ul>

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+8)@125 °C	81.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	57.5 ± 2.0	wt %	ASTM D3900
ENB Contents	8.9 ± 0.5	wt %	ASTM D6047

### Other Products Features

<b>Product Form</b>	Bale
<b>Packaging</b>	25 kg/Bale in Carton/Mesh Box, LDPE/EOM film, 750 kg(25 kg × 30)
<b>Shelf Life</b>	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
<b>The Others</b>	RoHS Free

### Contact Information

<b>Head Office</b>	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
<b>Plant</b>	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
<b>Revision Date</b>	12/02/2020
<b>Revision No.</b>	10