

Ethylene Propylene Rubber

KUMHO POLYCHEM

Product Data Sheet

| Product Description | Features |
|---|--|
| KEP0530 is an EPM rubber with Narrow molecular weight distribution, low ethylene. It can be used to Viscosity Index Improver. | <ul style="list-style-type: none">- Low Mooney Viscosity EPM Grade- Amorphous |

| Test items | Sale Specifications | Unit | Test Method |
|------------------------------------|---------------------|------|-------------|
| Volatile Matter | Max 1.50 | wt % | ASTM D5668 |
| Mooney Viscosity ML(1+4)@100 °C | 30.0 ± 5.0 | MU | ASTM D1646 |
| Ethylene Contents | 50.0 ± 2.0 | wt % | ASTM D3900 |

Other Products Features

| | |
|---------------------|---|
| Product Form | Bale |
| Packaging | 25 kg/Bag in Metal Box, EOM film, 750 kg(25 kg × 30) |
| Shelf Life | 24 months from date of production at room temperature in dry condition, exposure to light has to be avoided |
| The Others | RoHS Free |

Contact Information

| | |
|----------------------|---|
| Head Office | 8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000 |
| Plant | 613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822 |
| Revision Date | 12/02/2020 |
| Revision No. | 4 |