

Ethylene Propylene Rubber

KUMHO POLYCHEM

Product Data Sheet

Product Description	Features
KEP070P is an EPM rubber with narrow molecular weight distribution, high ethylene contents, When blended with polypropylene it can be used to injection molding, films, Sheets and polyolefin modifiers.	<ul style="list-style-type: none">- High MFR/ High impact resistance- Improve crack resistance, temperature flexibility, weather resistance in the modification of polyolefin thermoplastics

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.20	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@100 °C	69.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	70.5 ± 3.0	wt %	ASTM D3900

Other Products Features

Product Form	Pellet
Packaging	25 kg/Bag in Mesh Box, 500 kg(25 kg × 20)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
Revision Date	05/01/2016
Revision No.	9