

## Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

### Product Data Sheet

Product Description	Features
KEP281F is an EPDM rubber with broad molecular weight distribution, high ethylene, medium ENB contents. It can be used to weather strip solid, Heat-resistance hose, window seals and Various type of automobile parts.	<ul style="list-style-type: none"><li>- High Mooney Viscosity/ high loadability</li><li>- High curing speed</li><li>- Improved productivity &amp; collapse resistance</li><li>- Characteristics suitable for weather strip</li></ul>

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+8)@125 °C	82.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	67.0 ± 3.0	wt %	ASTM D3900
ENB Contents	5.7 ± 1.0	wt %	ASTM D6047

### Other Products Features

<b>Product Form</b>	Bale
<b>Packaging</b>	25 kg/Bag in Mesh/Carton/MB5 Box, LDPE film, 900 kg(25 kg × 36)
<b>Shelf Life</b>	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
<b>The Others</b>	RoHS Free

### Contact Information

<b>Head Office</b>	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
<b>Plant</b>	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
<b>Revision Date</b>	05/01/2016
<b>Revision No.</b>	9