

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

| Product Description | Features |
|--|--|
| KEP282F is an EPDM rubber with Medium molecular weight distribution, High ethylene , High ENB contents. It can be used to Weather strip solid, heat-resistance hose, window seal, Various types of automobile parts. | <ul style="list-style-type: none">- High loadability.- High curing speed- Improved productivity & Collapse resistance- Suitable for weather strip solid |

| Test items | Sale Specifications | Unit | Test Method |
|------------------------------------|---------------------|------|-------------|
| Volatile Matter | Max 0.75 | wt % | ASTM D5668 |
| Mooney Viscosity ML(1+8)@125 °C | 90.0 ± 5.0 | MU | ASTM D1646 |
| Ethylene Contents | 73.0 ± 2.0 | wt % | ASTM D3900 |
| ENB Contents | 5.7 ± 1.0 | wt % | ASTM D6047 |

Other Products Features

| | |
|---------------------|---|
| Product Form | Bale |
| Packaging | 25 kg/Bag in Carton & Mesh Box, LDPE film, 750kg(25kg × 30) |
| Shelf Life | 24 months from date of production at room temperature in dry condition, exposure to light has to be avoided |
| The Others | RoHS Free |

Contact Information

| | |
|----------------------|---|
| Head Office | 8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000 |
| Plant | 613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822 |
| Revision Date | 05/01/2016 |
| Revision No. | 3 |