

## Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

### Product Data Sheet

Product Description	Features
KEP902N is an oil extended EPDM rubber with narrow molecular weight distribution, high ethylene contents. It can be used to window seal, molding in general, shock absorbing moldings in general, shock absorbing Rubber(muffler hanger & engine mount)	<ul style="list-style-type: none"><li>- High loadability</li><li>- good physical properties</li><li>- Superior processability</li><li>- Characteristics suitable for low hardness</li></ul>

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+8)@125 °C	52.0 ± 4.0	MU	ASTM D1646
Ethylene Contents	66.5 ± 2.0	wt %	ASTM D3900
ENB Contents	4.5 ± 0.4	wt %	ASTM D6047
Oil Contents	100.0 ± 4.0	phr	Internal Method

### Other Products Features

<b>Product Form</b>	Bale
<b>Packaging</b>	25 kg/Bale in Carton/Mesh Box, LDPE Black film 900 kg(25 kg × 30)
<b>Shelf Life</b>	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
<b>The Others</b>	RoHS Free

### Contact Information

<b>Head Office</b>	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
<b>Plant</b>	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
<b>Revision Date</b>	06/01/2016
<b>Revision No.</b>	8