

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description	Features
KEP9570E is an oil extended EPDM rubber with bimodal molecular weight distribution with low ethylene content and high diene level. It can be used to Weather strip seal, CV sponge.	<ul style="list-style-type: none">- Excellent Sponge properties- Superior process-ability- Good curing performance- Ultra fast curing- Improve productivity & collapse resistance

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+8)@125 °C	70.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	55.0 ± 2.0	wt %	ASTM D3900
ENB Contents	10.0 ± 0.5	wt %	ASTM D6047
Oil Contents	20.0 ± 3.0	Phr	Internal Method

Other Products Features

Product Form	Bale
Packaging	25 kg/Bale in Carton/Mesh Box, LDPE film, 750 kg(25 kg × 30)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
Revision Date	06/08/2018
Revision No.	1